

# F-B24V

## ENCLOSURE TYPE POWER SUPPLY



### Product Features

- AC-DC Power Supply with Metal Enclosure.
- Fuse protected distribution.
- Power ON LED, Power indicator.

### Technical Specifications

Model	F-B24V5A	F-B24V10A	F-B24V15A
DC Output Voltage	24V DC		
Output Voltage Range	±3%		
Output Current	0~5A	0~10A	0~15A
DC Output Power	120W Max	240W Max	360W Max
Output Channel	9 Channels	18 Channels	18 Channels
AC input voltage range	100~260V AC (50~60Hz)		
Input current	3.5A Max		
Loaded efficiency	≥84%		
Input impulse current	Less than 60A, cold start		
Output overcurrent protection	120% ~150% of rated output power. Protection mode: hiccup mode, automatic recovery after the abnormal load condition is removed		
Output short circuit protection	Protection mode: hiccup mode, automatic recovery after the short-circuit condition is removed		
Isolation resistance	Input-Output: 500V DC or 2121V DC Input-FG: 500V DC or 2121V DC Output-FG: 500V DC or 707V DC Leakage Current ≤ 5mA MAX		
Output indication	LED power indicator		
Net weight	1.8kg	2.3kg	2.4kg
Gross weight	2kg	2.5kg	2.6kg
Dimension	315*215*62mm	315*215*62mm	315*215*62mm
Environment	FAN Cooling, Working Humidity: 20~90% , Storage Temp. and Humidity:-20°C~55°C ,10~95%RH, Vibration: 10~500Hz, 5G 10min./cycle, 60min.each along X,Y,Z axis		